

Tarkett

MSDS # 08102NM

THE FLOORING GROUP OF SWEDISH MATCH.

P.O. Box 300
Johnson City, TN
37605-0300

MATERIAL SAFETY DATA SHEET

Replaces NPCA-1-72

EMERGENCY TELEPHONE NO.
615-928-3122

DATE OF PREPARATION

10/19/87

*NIOSH/OSHA approved respirator required if TLV is exceeded.

SECTION I - PRODUCT IDENTIFICATION

CASNUMBER

(Is not a carcinogen)

PRODUCT NAME Tarkett Mark 10C AdhesivePRODUCT CLASS Hardwood Flooring Adhesive

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	OCCUPATIONAL EXPOSURE LIMITS		VAPC PRESSURE
		TVL	PEL	
Toluene (108-83-3)	Less than 1.75%	100 p.p.m.	200 p.p.m.	N. A.
Dibutyl Phthalate (84-74-2)	Less than 1.70%	5 mg./m ³	5 mg./m ³	N. A.

SECTION III - PHYSICAL DATA

BOILING RANGE% VOLATILE VOLUME

ca. 212° F.

ca. 33.5%

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION	OSHA <u>N.A.</u>	FLASHPOINT	LEL
	DOT <u>N.A.</u>	Indeterminate	<u>N. A.</u>

EXTINGUISHING MEDIA: Water

UNUSUAL FIRE AND EXPLOSION HAZARDS:

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Can cause eye irritation, redness and blurred vision. Prolonged or repeated contact with skin can cause irritation. Excessive inhalation can cause nasal and respiratory irritation. Swallowed can cause gastrointestinal irritation, nausea, vomiting, diarrhea. Long term exposure could cause lung, kidney, heart and liver complications.

2051520624

Page 2 of 3

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Not Known

PRIMARY ROUTE(S) OF ENTRY: ☒ DERMAL ☒ INHALATION ☐ INGESTION

EMERGENCY AND FIRST AID PROCEDURES: Use soap and water to wash from hands or other skin areas. Eye contamination should be immediately followed by flushing eye with cold water then consult physician. Inhalation: Anyone experiencing dizziness should leave area permanently for the day.

SECTION VI - REACTIVITY DATA

STABILITY: ☐ UNSTABLE ☒ STABLE

HAZARDOUS POLYMERIZATION: ☐ MAY OCCUR ☒ WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Unknown and if existent would require extremely high temperatures.

CONDITIONS TO AVOID: N.A.

INCOMPATIBILITY (MATERIALS TO AVOID) Strong acids which can create effervescence due to liberation of CO₂ from decomposition of chalk filler

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Small Spill: Clean up with absorbent material.

Large Spill: Use absorbent material and avoid contact, flush with water if possible.

WASTE DISPOSAL: Material disposal should be made in accordance with local state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: If T.L.V. levels are exceeded use chemical fume hood accepted by NIOSH/OSHA standards.

VENTILATION: Local Exhaust

PROTECTIVE GLOVES: Yes

EYE PROTECTION: Yes

OTHER PROTECTIVE EQUIPMENT: None Required

2051520025

Page 3 of 3

HYGIENIC PRACTICES: See Section V First Aid Procedures.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store at room temperature but not below 40°F in order to avoid freezing which can result in irreversible phase separation.

OTHER PRECAUTIONS: None

2051520026