

105 2497
105 2513EASTMAN KODAK COMPANY
APPROVED BY U.S. DEPARTMENT OF LABOR
"ESSENTIALLY SIMILAR" TO FORM OSHA-20

900370

MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME:

SIZE: 500 g. & 3 kg.

CHEMICAL NAME: Decyl Alcohol

SCD NO. = 00370
ACC NO. = 900370
MI# = R-0107.000
CAS REG. NO. = 112-30-1
PHONE NO.: (716) 722-5151FORMULA: $\text{CH}_3(\text{CH}_2)_9\text{OH}$

MANUFACTURER: Eastman Kodak Company

ADDRESS: 343 State Street, Rochester, New York 14650

FOR INFORMATION ON HEALTH HAZARDS CALL: (716) 722-5151

INFORMATION EFFECTIVE AS OF: 8-22-73

SECTION II HAZARDOUS INGREDIENTS OF MIXTURES

PRINCIPAL HAZARDOUS COMPONENT (S)	%	TLV (Units)

SECTION III PHYSICAL DATA

BOILING POINT (°F.)	451 F	SPECIFIC GRAVITY (H ₂ O=1)	0.83
VAPOR PRESSURE (mm Hg.)	1mm 204°F	PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)	4.83	EVAPORATION RATE (_____=1)	
SOLUBILITY IN WATER	Insoluble in water		
APPEARANCE AND ODOR	Viscous liquid		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	180°F (Open cup)	FLAMMABLE LIMITS	Lel	Uel

EXTINGUISHING MEDIA CO₂, dry chemical

SPECIAL FIRE FIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

2057486196

SECTION V HEALTH HAZARD DATA**THRESHOLD LIMIT VALUE**

None assigned by A.C.G.I.H.

EFFECTS OF OVEREXPOSURE

A moderate skin irritant.

EMERGENCY AND FIRST AID PROCEDURES

In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes; for eyes, get medical attention.

SECTION VI REACTIVITY DATA**STABILITY**

UNSTABLE

STABLE

X

CONDITIONS TO AVOID**INCOMPATIBILITY**

(Materials to avoid) Avoid contact with oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS**HAZARDOUS POLYMERIZATION****CONDITIONS TO AVOID**

May Occur

Will Not Occur

X

SECTION VII SPILL OR LEAK PROCEDURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Wearing suitable protective clothing, absorb spilled material on vermiculite. Place in fiber carton. Incinerate. Wash spill area well with soap and water.

WASTE DISPOSAL METHOD

Mix with flammable solvent, spray into incinerator equipped with afterburner and scrubber. State and local laws take precedence.

SECTION VIII SPECIAL PROTECTION INFORMATION**RESPIRATORY PROTECTION**
(Specify type)**VENTILATION**

LOCAL EXHAUST

X

MECHANICAL (general)

X

SPECIAL

OTHER

PROTECTIVE GLOVES

Rubber

EYE PROTECTION

Safety goggles

OTHER PROTECTIVE EQUIPMENT**SECTION IX SPECIAL PRECAUTIONS****PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING****OTHER PRECAUTIONS**